

Pumps

23 products

Catalogue generated 04/09/2026, 15:32

Photo	Product	Specifications
	LEO APM110 LEO · APM110 Peripheral pump	Power: 1.1 kW (1.5 HP) Phase: Single phase / Monophasé Max head: 85 m Max flow: 4.2 m³/h (70 L/min) Max suction: 8 m Max liquid temp.: 60 °C Protection: IPX4
	LEO APM150 LEO · APM150 Peripheral pump	Power: 1.5 kW (2.0 HP) Phase: Single phase / Monophasé Max head: 90 m Max flow: 4.8 m³/h (80 L/min) Max suction: 8 m Max liquid temp.: 60 °C Protection: IPX4
	LEO XKM60-1 LEO · XKM60-1 Peripheral pump	Power: 0.37 kW (0.5 HP) Voltage/Freq.: 230 V / 50 Hz Max head: 40 m Max flow: 40 L/min (2.4 m³/h) Inlet / Outlet: 1" Phase: Single phase / Monophasé
	LEO XKM70-1 LEO · XKM70-1 Peripheral pump	Power: On request Voltage/Freq.: 230 V / 50 Hz Max head: On request Max flow: On request Inlet / Outlet: 1" Phase: Single phase / Monophasé
	LEO XKM80-1 LEO · XKM80-1 Peripheral pump	Power: 0.75 kW (1.0 HP) Voltage/Freq.: 230 V / 50 Hz Max head: 70 m Max flow: 60 L/min Inlet / Outlet: 1" Max suction: 6 m
	LEO PQ50E-1 LEO · PQ50E-1 Automatic booster pump	Power: 0.37 kW (0.5 HP) Voltage/Freq.: 180-220 V / 50 Hz Max head: 30 m Max flow: 33 L/min Inlet / Outlet: 1" Max liquid temp.: 40 °C

Photo	Product	Specifications
	LEO ACM37 LEO · ACM37 Centrifugal pump	Power: 0.37 kW (0.5 HP) Phase: Single phase / Monophasé Max head: 23 m Max flow: 5.4 m³/h (90 L/min) Max suction: 8 m Max liquid temp.: 60 °C
	LEO ACM75 LEO · ACM75 Centrifugal pump	Power: 0.75 kW (1.0 HP) Phase: Single / Three phase Max head: 36 m Max flow: 6.0 m³/h (100 L/min) Max suction: 8 m Max liquid temp.: 60 °C
	LEO 2ACM150 LEO · 2ACM150 Multistage centrifugal pump	Power: 1.5 kW (2.0 HP) Voltage: 220-230 V Max head: 55 m Max flow: 130 L/min (7.8 m³/h) Max suction: 8 m Inlet / Outlet: 1½" / 1"
	LEO XCM170-1 LEO · XCM170-1 Stainless-steel multistage centrifugal pump	Power: On request Max head: On request Max flow: On request Body: Stainless steel AISI 304 / Inox 304
	LEO AJM75H LEO · AJM75H Self-priming jet pump	Power: 0.75 kW (1.0 HP) Max head: 50 m Max flow: 2.8 m³/h (47 L/min) Type: Self-priming / Auto-amorçante Max liquid temp.: 60 °C
	LEO AJM110H LEO · AJM110H Self-priming jet pump	Power: 1.1 kW (1.5 HP) Max suction: 9 m Max head: On request Max flow: On request Type: Self-priming / Auto-amorçante Max liquid temp.: 60 °C
	LEO AKS-751PWH LEO · AKS-751PWH Dirty-water submersible pump	Rated power: 750 W Max head: 8 m Max flow: 14 m³/h Max immersion: 7 m Max particle: 35 mm Outlet: 1½" Protection: IPX8 Automatic: Float switch / Flotteur
	LEO LKS-300P LEO · LKS-300P Rain-barrel submersible pump	Rated power: 300 W Max head: 11 m Max flow: 2.2 m³/h Max immersion: 7 m Max particle: 1 mm Outlet: 3/4" Protection: IPX8 Automatic: Float switch / Flotteur
	LEO STK50F LEO · STK50F Submersible peripheral pump	Voltage: 220-240 V Power: 0.37 kW (0.5 HP) Max flow: 40 L/min (2.4 m³/h) Max head: 35 m Max immersion: 10 m Outlet: 1"
	LEO QDX1.5-32-0.75LA LEO · QDX1.5-32-0.75LA Submersible drainage pump	Power: 0.75 kW Max head: 32 m Max flow: 9 m³/h (150 L/min) Type: Submersible / Submersible Automatic: Float switch / Flotteur

Photo	Product	Specifications
	LEO LSWM100A LEO · LSWM100A Submersible sewage pump	Power: 0.75 kW (1.0 HP) Voltage/Freq.: 180-220 V / 50 Hz Max flow: 19 m³/h Max head: 17 m Max particle: 25 mm Outlet: G2 (2")
	LEO LSWM150A LEO · LSWM150A Submersible sewage pump	Power: 1.1 kW (1.5 HP) Voltage/Freq.: 180-220 V / 50 Hz Max flow: 26 m³/h Max head: 13.5 m Max particle: 30 mm Outlet: G2 (2")
	LEO XKP1104E LEO · XKP1104E Swimming-pool pump	Power: 1.1 kW (1.5 HP) Voltage/Freq.: 220-240 V / 50 Hz Max flow: 375 L/min (22.5 m³/h) Max head: 15 m Max suction: 3.5 m Inlet / Outlet: 2" (50 mm) Max liquid temp.: 35 °C
	LEO XKP1604E LEO · XKP1604E Swimming-pool pump	Power: 1.6 kW (2.2 HP) Voltage/Freq.: 220-240 V / 50 Hz Max flow: 450 L/min (27 m³/h) Max head: 17 m Max suction: 3.5 m Inlet / Outlet: 2"×2" (50 mm) Max liquid temp.: 35 °C
	Bison Petrol Water Pump BS20 Bison · BS20 Petrol Water Pump	2 inch Gasoline water pump Outlet diameter: 50mm pump lift: 28m Flux: 36 • Engine model:170F • Horse Power: 7.0HP Starting system: recoil start Type: Single Cylinder,
	Bison Petrol Water Pump BS30 Bison · BS30 Petrol Water Pump	3 inch Gasoline water pump Outlet diameter: 80mm pump lift: 30M Suction Height: 7M Flux: 50M3/H Engine model:168F-1 Displacement: 196CC Starting system: recoil start
	Bison Petrol Water Pump BS40 Bison · BS40 Petrol Water Pump	4 inch Gasoline water pump Outlet diameter: 100mm pump lift: 30M Suction Height: 7M Flux: 60M3/H Engine model:170F Displacement: 210CC Starting system: recoil start